



PHYSICAL

CONDUCTORS: 28 AWG 7/36 Tinned Copper
 INSULATION: .010" Gray PVC with Red Edge
 Wrap: .001" Polyester Tape (Spiral)
 JACKET: .030" Black PVC
 TEMP. RATING: -20°C TO 105°C

ELECTRICAL

IMPEDANCE: 95 Ohms
 CAPACITANCE: 19 pF/ft @1MHz NOM
 CURRENT RATING: 1.3 A @ 10°C Rise
 Above Ambient
 VOLTAGE RATING: 300 V
 INSULATION RES: 10^{10} Ohms per 10 ft minimum
 APPROVALS: UL Listed Type CL2
 CSA Certified AWM FT-1
 Above Values Calculated in the Ground-Signal-Ground with
 Shield also Grounded.

All Dimensions in Inches Unless Otherwise Noted.

Part Number	Count	A Span, Inches(mm)	B Span, Inches(mm)	Ref Dia
159-2801-209	9	.450(11,43) Nom	.400 \pm 0.007(10,16 \pm 0,18)	.270
159-2801-210	10	.500(12,70) Nom	.450 \pm 0.007(11,43 \pm 0,18)	.270
159-2801-214	14	.700(17,78) Nom	.650 \pm 0.007(16,51 \pm 0,18)	.290
159-2801-215	15	.750(19,05) Nom	.700 \pm 0.011(17,78 \pm 0,28)	.300
159-2801-216	16	.800(20,32) Nom	.750 \pm 0.011(19,05 \pm 0,28)	.310
159-2801-220	20	1.000(25,40) Nom	.950 \pm 0.011(24,13 \pm 0,28)	.330
159-2801-224	24	1.200(30,48) Nom	1.150 \pm 0.011(29,21 \pm 0,28)	.350
159-2801-225	25	1.250(31,75) Nom	1.200 \pm 0.011(30,48 \pm 0,28)	.360
159-2801-226	26	1.300(33,02) Nom	1.250 \pm 0.011(31,75 \pm 0,28)	.360
159-2801-234	34	1.700(43,18) Nom	1.650 \pm 0.011(41,91 \pm 0,28)	.400
159-2801-236	36	1.800(45,72) Nom	1.750 \pm 0.015(44,45 \pm 0,38)	.410
159-2801-237	37	1.850(46,99) Nom	1.800 \pm 0.015(45,72 \pm 0,38)	.410
159-2801-240	40	2.000(50,80) Nom	1.950 \pm 0.015(49,53 \pm 0,38)	.430
159-2801-250	50	2.500(63,50) Nom	2.450 \pm 0.015(62,23 \pm 0,38)	.480
159-2801-260	60	3.000(76,20) Nom	2.950 \pm 0.015(74,93 \pm 0,38)	.520
159-2801-264	64	3.200(81,28) Nom	3.150 \pm 0.015(80,01 \pm 0,38)	.530

DRAWN	PROD ENG	QA	MKT	P/ECN#	DRAWING NO.	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872		Rev K
FITS 4/16/03					TITLE: Round 'N' Flat® Jacketed Cable			SHEET
								1 of 1