

PNP Transistor

6501130 NATL SEMICOND, (DISCRETE)

28C 35443

D

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES



Type No.	Case Style	V _{CEO} (V) Min	V _{CE0} (V) Min	V _{BE0} (V) Min	ICES* ICBO (mA) Max	hFE Min Max @ I _C (mA) & V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min Max	I _C (mA) @ I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) @ I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
2N722	TO-18	50	35	5	100	30 90 150 5 10	1.5	1.3	150	45	60	50				63
2N1132	TO-5	50	35	2	100	30 90 150 5 10	1.5	1.3	150	45	60	50				63
2N2696	TO-18	25	25		25	20 300 2	0.25	1.1	50	20	100	50	170		1	63
2N2904	TO-5	60	40	5	20	20 500 10 40 120 150 10 35 10 10 25 1 10 20 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2904A	TO-5	60	60	5	10	40 500 10 40 150 10 40 10 10 40 120 1 10 40 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2905	TO-5	60	40	5	20	30 500 10 100 300 150 10 75 10 10 50 1 10 35 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2905A	TO-5	60	60	5	10	50 500 10 100 300 150 10 100 10 10 100 1 10 75 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2906	TO-18	60	40	5	20	20 500 10 40 120 150 10 35 10 10 25 1 10 20 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2906A	TO-18	60	60	5	10	40 500 10 40 120 150 10 40 10 10 40 1 10 40 0.1 10	0.4	1.3	150	8	200	50	100		2	63
2N2907	TO-18	60	40	5	20	35 500 10 100 300 150 10 75 10 10 50 1 10 35 0.1 10	0.4	1.3	150	8	200	50	100		2	63

6501130 NATL SEMICOND, (DISCRETE)

28C 35444

D

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES (Continued)



Type No.	Case Style	V _{CEO} (V) Min	V _{CE0} (V) Min	V _{BE0} (V) Min	I _{CEO} (mA) Max	I _{CB0} (mA) Max	h _{FE}		I _C & V _{CE} (V)	V _{CE(SAT)} V _{BE(SAT)} (V)		I _C (mA)	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA)	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
							Min	Max		Max	Min								
2N3072A	TO-18	60	60	5	10	50	500	10	10	0.4	1.3	150	8	200	50	100		2	63
2N3072	TO-5	60	60	4	10*	15	300	2	1	0.25	1.2	50	10	130	50	100		3	63
2N3073	TO-18	60	60	4	10*	15	300	2	1	0.25	1.2	50	10	130	50	100		3	63
2N3120	TO-5	45	45	4	10*	30	130	50	1	1.0	2.0	300	10	130	50	100		4	63
2N3121	TO-18	45	45	4	10*	15	300	2	1	0.25	1.2	50	10	130	50	100		4	63
2N3133	TO-5	50	35	4	50	10	150	1	10	0.6	1.5	150	10	200	50	150		2	63
2N3134	TO-5	50	35	4	50	50	150	1	10	0.6	1.5	150	10	200	50	150		2	63
2N3135	TO-18	50	35	4	50	25	150	1	10	0.6	1.5	150	10	200	50	150		2	63
2N3136	TO-18	50	35	4	50	25	150	1	10	0.6	1.5	150	10	200	50	157		2	63
2N3502	TO-5	45	45	5	10	50	500	10	10	0.25	1.0	50	8	200	50	100	4	4/7	63

TEST CONDITIONS:

(1) I_C = 300 mA, V_{CC} = 10V, I_B¹ = I_B² = 30 mA, (2) I_C = 150 mA, V_{CC} = 6V, I_B¹ = I_B² = 15 mA, (3) I_C = 300 mA, V_{CC} = 15V, I_B¹ = I_B² = 30 mA, (4) I_C = 300 mA, V_{CC} = 30V, I_B¹ = I_B² = 30 mA, (5) I_C = 10 mA, V_{CC} = 3V, I_B¹ = I_B² = 1 mA, (6) I_C = 100 μA, V_{CE} = 5V, f = 100 Hz, (7) I_C = 30 μA, V_{CE} = 5V, f = 1 kHz, (8) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz, (9) I_C = 250 μA, V_{CE} = 5V, f = 1 kHz, (10) I_C = 10 μA, V_{CE} = 5V, f = 1 kHz, (11) I_C = 50 mA, V_{CC} = 30V, I_B¹ = I_B² = 5 mA, (12) I_C = 150 mA, V_{CC} = 30V, I_B¹ = I_B² = 15 mA, (13) I_C = 50 mA, V_{CC} = 10V, I_B¹ = I_B² = 5 mA.

PNP Transistors

2

PNP Transistors

6501130 NATL SEMICOND, (DISCRETE)

28C 35445 D

GENERAL PURPOSE AMPS AND SWITCHES (Continued)



Type No.	Case Style	V _{CEO} (V)		V _{BEBO} (V)		V _{CE(SAT)} & V _{BE(SAT)} (V)		h _{FE} @ I _C (mA) & V _{CE} (V)		V _{CE(SAT)} (V) & V _{BE(SAT)} (V)		I _C (mA)		C _{ob} (pF) Max	f _T (MHz)		t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.		
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		Min	Max						
2N3503	TO-5	60	60	5	50	10	0.25	10	500	10	1	50	8	200	4	63	4/7	63				
																			140	10	1.3	150
																			135	1	2	300
2N3504	TO-18	45	45	5	30	10	1.6	10	500	10	2	500	8	200	4	63	4/7	63				
																			100	10	1.3	150
																			140	1	2	300
2N3505	TO-18	60	60	5	50	10	1.6	10	500	10	2	500	8	200	4	63	4/7	63				
																			115	10	1.3	150
																			140	1	2	300
2N3638	TO-92 (92)	Same as PN3638, see page 2-13 for explanation																				
2N3638A	TO-92 (92)	Same as PN3638A, see page 2-13 for explanation																				
2N3644	TO-92 (92)	Same as PN3644, see page 2-13 for explanation																				
2N3645	TO-92 (92)	60	60	5	40	10	0.4	10	0.1	10	0.8	150	8	200	20	63	4/7	63				
																			80	1	1.3	300
																			100	10	2	300
2N3702	TO-92 (94)	40	25	5	100	5	0.25	5	60	5	50	12	100	50	63	4/7	63					
																		30	150	50		
2N3703	TO-92 (94)	Same as PN4142, see page 2-13 for explanation																				
2N4142	TO-92 (92)	Same as PN4142, see page 2-13 for explanation																				
2N4143	TO-92 (92)	Same as PN4143, see page 2-13 for explanation																				
2N4290	TO-92 (94)	30	20	5	500	20	0.4	10	100	10	1.5	100	10	100	10	63	4/7	63				
																			40	10	10	

T-29-01

6501130 NATL SEMICOND, (DISCRETE)

28C 35446

D

GENERAL PURPOSE AMPS AND SWITCHES (Continued)



Type No.	Case Style	V _{CEO} (V) Min	V _{CE0} (V) Min	V _{BE0} (V) Min	I _{CBO} (mA) Max	I _{CB0} @ V _{CB} (V) Max	h _{FE} Min	I _C @ V _{CE} (mA) & V _{CE} (V)	V _{CE(SAT)} V _{BE(SAT)} (V) & (V) @ I _C (mA)		C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) @ f _T Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Max	Min							
2N4291	TO-92 (94)	40	30	6	200	30	100	100 300	0.4	1.5	10	100	10				63
2N4402	TO-92 (94)	40	40	5 *			20 50 30	500 150 10	0.4	0.7 0.95	10	150	20	255		4	63
2N4403	TO-92 (92)	40	40	5			20 100 60	500 150 10	0.4	0.75 0.95	10	200	20	255		4	63
2N4971	TO-92 (92)	Same as PN2906, see page 2-12 for explanation															
2N4972	TO-92 (92)	Same as PN2907, see page 2-12 for explanation															
2N5142	TO-92 (92)	Same as PN5142, see page 2-14 for explanation															
2N5143	TO-92 (92)	Same as PN5143, see page 2-14 for explanation															
2N5221	TO-92 (92)	15	15	3	100	10	30	600 50	0.5	1.1	15	100	20				63
2N5226	TO-92 (92)	25	25	4	300	15	30	600 50	0.8	1.0	20	50	20				63
2N5354	TO-92 (94)	25	25	4	100	25	40	120 50	0.25		8						63
2N5355	TO-92 (94)	25	25	4	100	25	100	300 50	0.25		8						63
2N5365	TO-92 (94)	40	40	4	100	40	20 40	300 50	0.25	1.1	8						63
2N5366	TO-92 (94)	40	40	4	100	40	40 300	50 1	0.25	2.0	8						63

T-29-01

TEST CONDITIONS:

(1) I_C = 300 mA, V_{CC} = 10V, I_B¹ = I_B² = 30 mA. (2) I_C = 150 mA, V_{CC} = 6V, I_B¹ = I_B² = 15 mA. (3) I_C = 300 mA, V_{CC} = 15V, I_B¹ = I_B² = 30 mA. (4) I_C = 300 mA, V_{CC} = 30V, I_B¹ = I_B² = 30 mA. (5) I_C = 10 mA, V_{CC} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 100 Hz. (7) I_C = 30 μA, V_{CE} = 5V, f = 1 kHz. (8) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 250 μA, V_{CE} = 5V, f = 1 kHz. (10) I_C = 10 μA, V_{CE} = 5V, f = 1 kHz. (11) I_C = 50 mA, V_{CC} = 30V, I_B¹ = I_B² = 5 mA. (12) I_C = 150 mA, V_{CC} = 30V, I_B¹ = I_B² = 15 mA. (13) I_C = 50 mA, V_{CC} = 10V, I_B¹ = I_B² = 5 mA.

2

PNP Transistors

PNP Transistors

6501130 NATL SEMICOND, (DISCRETE)

28C 35447 D

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES (Continued)

Type No.	Case Style	V _{CEO} (V) Min	V _{CEO} (V) Max	V _{ESD} (V) Min	V _{ESD} (V) Max	I _{CB0} * (mA) Min	I _{CB0} * (mA) Max	V _{CB} (V)	h _{FE} Min	h _{FE} Max	I _C (mA) Min	I _C (mA) Max	V _{CE(SAT)} (V) Min	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	V _{BE(SAT)} (V) Max	I _C (mA) Min	I _C (mA) Max	f _T (MHz) Min	f _T (MHz) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
2N5447	TO-92 (97)	40	25	5					60	300	50	50	0.25				100	100						63
2N5817	TO-92 (97)	50	40	5		100	25	25	25	500	2	500	0.75		1.2		100	100						63
MPS3638	TO-92 (92)	Same as PN3638, see page 2-13 for explanation																						
MPS3638A	TO-92 (92)	Same as PN3638A, see page 2-13 for explanation																						
MPS3644	TO-92 (92)	Same as PN3644, see page 2-13 for explanation																						
MPS3645	TO-92 (92)	Same as PN3645, see page 2-13 for explanation																						
MPS3702	TO-92 (92)	40	25	5		100	20	20	60	300	50	50	0.25				100	100						63
MPS3703	TO-92 (92)	50	30	5		100	20	20	30	150	50	50	0.25				100	100						63
MPS6533	TO-92 (92)	40	40	4		50	30	30	25	500	10	500	0.5		1.0									63
MPS6534	TO-92 (92)	40	40	4		50	30	30	90	270	100	100	0.3		1.0									63
MPS6535	TO-92 (92)	30	30	4		100	20	20	30	100	1	100	0.5		1.2									63
PN2906	TO-92 (92)	60	40	5		20	50	50	20	500	10	500	0.4		1.3		200	200			100		2	63
PN2906A	TO-92 (92)	60	60	5		10	50	50	40	120	10	150	0.4		1.3		200	200			100		2	63
PN2907	TO-92 (92)	60	40	5		20	50	50	30	500	10	500	0.4		1.3		200	200			100		2	63
									75	300	10	150	1.6		2.6									63
									50	10	10	500	1.6		2.6									63
									35	0.1	10	10	0.4		1.3									63

6501130 NATL SEMICOND, (DISCRETE)

28C 35448

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES (Continued)

Type No.	Case Style	VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO @ (mA) Max	VCE @ IC & VCE (V)	hFE @ IC (mA) Min Max	VCE(SAT) VBE(SAT) (V) & Min Max	IC (mA) @ Min Max	Cob (pF) Max	ft (MHz) Min Max	IC (mA) @ Min Max	toff (ns) Max	NF (dB) Max	Test Conditions	Process No.
PN2907A	TO-92 (92)	60	60	5	20	50	100 300	0.4	1.3 150	8	200	50	100		2	63
PN3638	TO-92 (92)	25	25	4	35*	15	20 300	0.25	1.1 50	20	100	50	170		1	63
PN3638A	TO-92 (92)	25	25	4	25*	15	20 300	0.25	1.1 50	10	150	50	170		1	63
PN3644	TO-92 (92)	45	45	5	35*	30	20 300	0.25	1.0 50	8	200	20	100		4	63
PN3645	TO-92 (92)	60	60	5	35*	50	20 300	0.25	1.0 50	8	200	20	100		4	63
PN4142	TO-92 (92)	60	40	5			20 500	0.4	1.3 150	8	200	50	100		12	63
PN4143	TO-92 (92)	60	40	5			20 500	0.4	1.3 150	8	200	50	100		12	63

TEST CONDITIONS:
 (1) IC = 300 mA, VCC = 10V, IB1 = IB2 = 30 mA, VCE = 30V, IB1 = IB2 = 30 mA, VCC = 30V, IB1 = IB2 = 30 mA.
 (2) IC = 150 mA, VCC = 10V, IB1 = IB2 = 15 mA, VCE = 30V, IB1 = IB2 = 15 mA, VCC = 30V, IB1 = IB2 = 15 mA.
 (3) IC = 300 mA, VCC = 15V, IB1 = IB2 = 30 mA, VCE = 30V, IB1 = IB2 = 30 mA, VCC = 30V, IB1 = IB2 = 30 mA.
 (4) IC = 300 mA, VCC = 15V, IB1 = IB2 = 30 mA, VCE = 30V, IB1 = IB2 = 30 mA, VCC = 30V, IB1 = IB2 = 30 mA.
 (5) IC = 10 mA, VCC = 3V, IB1 = IB2 = 1 mA, VCE = 5V, f = 1 kHz, (7) IC = 30 mA, VCE = 5V, f = 1 kHz, (8) IC = 100 mA, VCE = 5V, f = 1 kHz, (9) IC = 250 mA, VCE = 5V, f = 1 kHz.
 (10) IC = 10 mA, VCE = 5V, f = 1 kHz, (11) IC = 50 mA, VCC = 30V, IB1 = IB2 = 5 mA, (12) IC = 150 mA, VCC = 30V, IB1 = IB2 = 15 mA, (13) IC = 50 mA, VCC = 10V, IB1 = IB2 = 5 mA.

PNP Transistors

2

6501130 NATL SEMICOND, (DISCRETE)

28C 35449 D

T-29-01

PNP Transistors

GENERAL PURPOSE AMPS AND SWITCHES (Continued)



Type No.	Case Style	V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} (mA) Max	I _{CE0} (mA) Max	I _{FE} (mA) Min	I _{CE} (mA) Max	V _{CE} (V) Max	V _{CE(SAT)} (V) & V _{BE(SAT)} (V)		I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
										Max	Min								
PN5142	TO-92 (92)	20	20	4	50*	12	15	300	10	0.5	1.5	50	10	100	50	200		1	63
PN5143	TO-92 (92)	20	20	4	50*	12	30	300	10	0.2	0.8	2.5	10	100	50	200		1	63
TIS91	TO-92 (94)	40	40	5	100	20	30	50	2	0.2	0.8	2.5							63
TIS93	TO-92 (97)	40	40	5	100	20	100	300	2	0.25	0.6	1.0							63
TIS93	TO-92 (97)	40	40	5	100	20	100	300	2	0.25	0.6	1.0							63
TN2904A	TO-237 (91)	60	60	5	10	50	40	0.1	10	0.4	1.3	150	8	200	50	100		2	63
TN2905	TO-237 (91)	60	40	5	20	50	30	500	10	0.4	1.3	150	8	200	50	100		2	63
TN2905A	TO-237 (91)	60	60	5	10	50	75	150	10	1.6	2.6	500							63
2N3250	TO-18	50	40	5			35	0.1	10	0.4	1.3	150	8	200	50	100		2	63
2N3251	TO-18	50	40	5			15	50	1	0.25	0.6	0.9	6	250	10	225	6	5/6	66
2N3905	TO-92 (92)	40	40	5			50	100	1	0.5	1.2	50	6	300	20	250	6	5/6	66
2N3905	TO-92 (92)	40	40	5			30	50	1	0.25	0.65	0.85	4.5	200	10	260	5	5/8	66

6501130 NATL SEMICOND, (DISCRETE)

28C 35450

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES (Continued)

Type No.	Case Style	VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES [*] ICBO @ (mA) Max	VCE (V)	hFE Min	IC @ (mA)	VCE(SAT) (V)		IC (mA)	Cob (pF) Max	fT (MHz) Min	fT (MHz) Max	IC (mA) Max	toff (ns) Max	NF (dB) Max	Test Conditions	Process No.	
									Max	Min										
2N3906	TO-92 (92)	40	40	5			30	100	0.25	0.65	10	4.5	250	10	300		4	5/8	66	
2N4121	TO-92 (92)	Same as PN4121, see page 2-16 for explanation																		
2N4122	TO-92 (92)	Same as PN4122, see page 2-16 for explanation																		
2N4125	TO-92 (92)	30	30	4	50	20	25	50	0.4	0.95	50	4.5	200	10			5	8	66	
2N4126	TO-92 (92)	25	25	4	50	20	60	50	0.4	0.95	50	4.5	250	10			4	8	66	
2N4916	TO-92 (92)	Same as PN4916, see page 2-16 for explanation																		
2N4917	TO-92 (92)	Same as PN4917, see page 2-16 for explanation																		
2N5138	TO-92 (92)	Same as PN5138, see page 2-16 for explanation																		
2N5139	TO-92 (92)	Same as PN5139, see page 2-16 for explanation																		
MPS3905	TO-92 (92)	40	40	5			30	0.1	0.25	0.65	10	4.5	200	10			5	8	66	
MPS3906	TO-92 (92)	40	40	5			60	1	0.4	0.95	50	4.5	250	10			4	8	66	
MPS6516	TO-92 (92)	40	40	4	50	30	30	100	0.5	0.95	50	4							66	
MPS6517	TO-92 (92)	40	40	4	50	30	60	100	0.5	0.95	50	4							66	

TEST CONDITIONS:
 (1) IC = 300 mA, VCC = 10V, IB¹ = IB² = 15 mA, VCE = 6V, IB¹ = IB² = 15 mA, VCC = 30V, IB¹ = IB² = 30 mA.
 (2) IC = 10 mA, VCC = 3V, IB¹ = IB² = 1 mA, VCE = 5V, f = 1 kHz. (7) IC = 100 μA, VCE = 5V, f = 1 kHz. (8) IC = 100 μA, VCE = 5V, f = 1 kHz. (9) IC = 250 μA, VCE = 5V, f = 1 kHz.
 (10) IC = 10 μA, VCE = 5V, f = 1 kHz. (11) IC = 50 mA, VCC = 30V, IB¹ = IB² = 5 mA, VCC = 150 mA, VCC = 30V, IB¹ = IB² = 5 mA, VCC = 10V, IB¹ = IB² = 5 mA.
 (12) IC = 150 mA, VCC = 30V, IB¹ = IB² = 15 mA, VCC = 15V, IB¹ = IB² = 15 mA, VCC = 30V, IB¹ = IB² = 30 mA.
 (13) IC = 300 mA, VCC = 30V, IB¹ = IB² = 30 mA, VCC = 30V, IB¹ = IB² = 30 mA.

D
PNP Transistors

2

6501130 NATL SEMICOND, (DISCRETE)

28C 35451 D

PNP Transistors

T-29-01

GENERAL PURPOSE AMPS AND SWITCHES (Continued)



Type No.	Case Style	V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} (mA) Max	I _{CB0} (mA) Max	h _{FE} Min	h _{FE} Max	I _C (mA) Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	f _{off} (Incl) Max	NF (dB) Max	Test Conditions	Process No.
MPS6518	TO-92 (92)		40	4	500	30	90	150	100	0.5		50	4						66
NS3905	TO-18	40	40	5			15	30	100	0.25	0.65	10	4.5	200	200	200	5	5/8	66
NS3906	TO-18	40	40	5			30	60	100	0.25	0.65	10	4.5	250	300	300	4	5/8	66
PN4121	TO-92 (92)	40	40	5	25*	30	15	70	50	0.13	0.75	1	4.5	400	150	150	4	11/8	66
PN4122	TO-92 (92)	40	40	5	25*	30	150	300	10	0.14	0.7	10	4.5	450	150	150	4	11/8	66
PN4916	TO-92 (92)	30	30	5	25*	15	15	70	50	0.13	0.75	1	4.5	400	150	150	4	13/8	66
PN4917	TO-92 (92)	30	30	5	25*	15	60	100	0.1	0.14	0.9	10	4.5	450	150	150	4	13/8	66
PN5138	TO-92 (92)	30	30	5	50	20	50	800	0.1	0.3	1.0	10	7	30	30				66
PN5139	TO-92 (92)	20	20	5	50*	15	15	40	10	0.2	0.7	10	5	300	200	200		13	66
ST3906	TO-92 (92)	40	40	5			60	100	0.1	0.5	0.75	50	4.5	250	250				66

6501130 NATL SEMICOND, (DISCRETE)

28C 35452 D

GENERAL PURPOSE AMPS AND SWITCHES (Continued)

Type No.	Case Style	V _{CEO} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} (mA) Max	I _{CB0} (mA) Max	I _{CE} (mA) & I _{CB} (mA)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.		
2N4354	TO-92 (92)	Same as PN4354, see below for explanation																		67
2N4355	TO-92 (92)	Same as PN4355, see below for explanation																		67
2N4356	TO-92 (92)	Same as PN4356, see page 2-18 for explanation																		67
2N5448	TO-92 (97)	50	30	5	100	20	30	150	50	5	0.25	100	50	50					67	
MPSA55	TO-92 (92)		60	4	100	60	50	100	1	100	0.25	50	100						67	
MPSA56	TO-92 (92)		80	4	100	80	50	100	1	100	0.25	50	100						67	
MPS4354	TO-92 (92)	Same as PN4354, see below for explanation																		67
MPS4355	TO-92 (92)	Same as PN4355, see below for explanation																		67
MPS4356	TO-92 (92)	Same as PN4356, see page 2-18 for explanation																		67
MPS6562	TO-92 (92)			5	100	20	50	200	500	1	0.5	30	500	10					67	
NS4234	TO-39		40		100 μA	40	40	100	1	1.5	0.6	300	100						67	
PN4354	TO-92 (92)	60	60	5	50	50	30	500	10	0.9	0.15	100	500	50	400	3	14/15		67	
PN4355	TO-92 (92)	60	60	5	50	50	75	500	10	0.9	0.15	100	500	50	400	3	14/15		67	

TEST CONDITIONS:

(1) I_C = 300 mA, V_{CC} = 10V, I_B¹ = I_B² = 30 mA, V_{CE} = 5V, f = 100 Hz. (2) I_C = 150 mA, V_{CC} = 6V, I_B¹ = I_B² = 15 mA. (3) I_C = 300 mA, V_{CC} = 15V, I_B¹ = I_B² = 30 mA. (4) I_C = 300 mA, V_{CC} = 30V, I_B¹ = I_B² = 30 mA. (5) I_C = 10 mA, V_{CC} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 30 μA, V_{CE} = 5V, f = 1 kHz. (8) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 250 μA, V_{CE} = 5V, f = 1 kHz. (10) I_C = 10 μA, V_{CE} = 5V, f = 1 kHz. (11) I_C = 50 mA, V_{CC} = 30V, I_B¹ = I_B² = 5 mA. (12) I_C = 150 mA, V_{CC} = 30V, I_B¹ = I_B² = 15 mA. (13) I_C = 50 mA, V_{CC} = 10V, I_B¹ = I_B² = 5 mA. (14) I_C = 500 mA, V_{CC} = 30V, I_B¹ = I_B² = 50 mA. (15) I_C = 100 μA, V_{CC} = 10V, f = 1 kHz.

T-29-01

PNP Transistors

2

6501130 NATL SEMICOND, (DISCRETE)

28C 35453 D

PNP Transistors

GENERAL PURPOSE AMPS AND SWITCHES (Continued)

Type No.	Case Style	VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO (mA) Max	VCB (V)	hFE @ IC & VCE		VBE(SAT) (V) & VCE(SAT) (V)		IC (mA) @ Min Max	Cob (pF) Max	fT (MHz)		IC (mA) @ Min Max	toff (ns) Max	NF (dB) Max	Test Conditions	Process No.
							Min	Max	Min	Max			Min	Max					
PN4356	TO-92 (92)	80	80	5	50	50	30	500	10	0.15	0.9	150	30	100	500	400	3	14/15	67
PN5447	TO-92 (92)	40	25	5	100	20	60	300	5	0.25	1.1	500	12	100	50				67
TN4036	TO-237 (91)	90	65	7	20	60	20	140	10	0.65	1.4	150	30	60	50				67
TN4037	TO-237 (91)	60	40	7	250	60	15	250	10	1.4		150	30	60	200	50			67
MPS6563	TO-92 (92)			5	100	20	50	200	1	0.5		350	30	60	10				68
2N6076	TO-92 (94)	25	25	5	100	25	100	500	10	0.25	0.8	10							71
2N5400	TO-92 (92)	130	120	5	100	100	40	180	5	0.2	1.0	10	6	100	400	10	8	9	74
2N5401	TO-92 (92)	160	150	5	50	120	30	50	5	0.5	1.0	50	6	100	300	10	8	9	74
MPSL51	TO-92 (92)	100	100	4	1 μA	50	40	250	5	0.25	1.2	10	8	60	10				74

TEST CONDITIONS:
 (1) IC = 300 mA, VCC = 10V, IB1 = IB2 = 30 mA, VCE = 6V, f = 1 kHz, (2) IC = 150 mA, VCC = 6V, IB1 = IB2 = 15 mA, VCE = 15V, IB1 = IB2 = 30 mA, VCC = 30V, IB1 = IB2 = 30 mA.
 (3) IC = 300 mA, VCC = 5V, f = 1 kHz, (4) IC = 300 mA, VCC = 5V, f = 1 kHz, (5) IC = 10 mA, VCC = 3V, IB1 = IB2 = 1 mA, (6) IC = 100 μA, VCE = 5V, f = 100 Hz, (7) IC = 30 μA, VCE = 5V, f = 1 kHz, (8) IC = 100 μA, VCE = 5V, f = 1 kHz, (9) IC = 250 μA, VCE = 5V, f = 1 kHz.
 (10) IC = 10 μA, VCE = 5V, f = 1 kHz, (11) IC = 50 mA, VCC = 30V, IB1 = IB2 = 5 mA, (12) IC = 150 mA, VCC = 30V, IB1 = IB2 = 15 mA, (13) IC = 50 mA, VCC = 10V, IB1 = IB2 = 5 mA, (14) IC = 500 mA, VCC = 30V, IB1 = IB2 = 50 mA, (15) IC = 100 μA, VCC = 10V, f = 1 kHz.

T-29-01